

Industrial / Spectacles / 5X7

5X7 - Clear Plus

Code: 5X7.03.11.00

Date: 06-07-26 1/2

5X7 is designed for a perfect integration with prescription glasses. The exclusive SoftPad technology, a high-strength insert combined with rod adjustments, ensure maximum stability even in extreme conditions.



Frame mark (EU)

Mod.5X7 U EN166 FT U EN175 FT CE

Lens mark (EU)

2C-1.2 U 1 FT K N CE

Frame technology

Overspec, Adjustment of temples in length, Rubber Terminal, Terminal tilting movement, SoftPad

Conditions of use

Standard brightness, Low brightness

Lens technology

Anti-Scratch + Anti-Fog (KN - Vanguard PLUS), UV400

Lens color

Clear

Lens material

Polycarbonate

Frame color

Gunmetal/Green

Standards

EN166, EN170

Scale number

(2C-1.2)

Mechanical resistance

Low energy impact (F)

Optional requirements

Resistance to surface damage by fine particles (K), Resistance to fogging of oculars (N), Protection against high speed particles at extreme temperatures -5°/+55° C (T)

Optical class

Optical class (I)

Weight

37g

>> <https://www.univetsafety.com/en/products/safety/spectacles/5x7/5x7-clear-plus/>



01.

UPPER FRONTAL

Grants comfort and stability with a shockproof effect

02.

SIDE SHIELDS

Improved peripheral protection even in combination with eyeglasses

03.

NO TEMPLES OVERLAPPING

Avoids the annoying overlapping of temples between the two glasses, for comfort and greater stability even in prolonged use

04.

RUBBER TERMINAL WITH TILTING MOVEMENT & LENGTH ADJUSTMENT

Allows to obtain the correct fit and work in constant safety

Attention! Any images on this page illustrate the frame technologies of the product family in question and may represent frame and lens colours that do not correspond to the product code of the following sheet.

HEADQUARTERS

Univet S.r.l. Via Giovanni Prati 87 25086 Rezzato - Telephone 030 2499411 - Fax 030 2499430 - info@univetsafety.com
VAT. IT02506570163