

# Product data sheet uvex silv-Air 7312 FFP3 R D



## **Product information**

Product features	<ul> <li>Particle-filtering cup shape mask with exhalation valve</li> <li>Protection level FFP 3</li> <li>Soft material edges for increased comfort</li> <li>Soft sealing lip guarantees a secure, comfortable sealed position of the mask</li> <li>Integrated, flexible, adjustable nose clip</li> <li>4-point headband attachment allows an individual and secure fit</li> <li>Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask</li> <li>Mask fulfils the requirements of reusability (R) and the dolomite dust test (D)</li> </ul>	
Materials	Headband: Headband clips: Nose clip: Filter/mask: Sealing lip: Valve:	textile Polypropylene metal, PP PP, Polyester synthetic foam PP
Weight	22 g	
Standard	EN 149:2001 + A1:20	009

#### **Versions & Accessories**

Article number	Colour/Version	Retail unit
8707.312	cup shape mask FFP3, white with valve	5 pcs. per box
8701.011	uvex clear cleaning spray	1 can, 360ml

## **Packaging sizes**

Box	approx. 190 x 160 x 150 mm
Outer Carton	approx. 610 x 400 x 310 mm

#### Maximum breathing resistance acc. to EN149 in mbar

	Inhalation resistance 301/min.	Inhalation resistance 951/min.	Exhalation resistance 1601/min.
FFP1	0,6	2,1	3,0
FFP2	0,7	2,4	3,0
FFP3	1,0	3,0	3,0

### Areas of use\*

bacteria, enzyme, nanoparticles.
----------------------------------

\*Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

All respiratory protective devices fall into PPE category III (high risks).

Uvex accepts no liability for any possible harm or damage which may result from this information. This data sheet does not replace a detailed risk assessment nor seeking specialist advise.

UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth