

Breathing Protection

02.03.2021

Product data sheet uvex silv-Air 2200 FFP2 NR D





Product information

Product features	 Particle-filtering cup shape mask without exhalation valve Protection level FFP2 Soft material edges for high wearing comfort Continuous head band for a comfortable and secure fit Flexible and adjustable nose clip Compatible with uvex safety eyewear Soft sealing lip guarantees a secure, comfortable sealed position of the mask Mask fulfils the requirements of the dolomite dust test (D) 	
Materials	Headband: textile Nose clip: aluminum Filter / mask: Melt Blown PP, Polyester Sealing lip: PVC foam	
Weight	12 g	
Standard	EN 149:2001 + A1:2009	

Versions

Article number	Colour/Version	Retail unit
8732.200	cup shape mask FFP2, white without valve	20 pcs. per box
8752.200	cup shape mask FFP2, white without valve	3 pcs. per bag

Packaging sizes

Box	approx. 135 x 135 x 230 mm
Outer Carton	approx. 560 x 430 x 260 mm

Maximum breathing resistance acc. to EN149 in mbar

	Inhalation resistance	Inhalation resistance	Exhalation resistance
	30I/min.	95I/min.	160I/min.
FFP1	0,6	2,1	3,0
FFP2	0,7	2,4	3,0
FFP3	1,0	3,0	3,0

Areas of use*

The respiratory protection mask can be	Woodworking, softwood, cement, metal,
used against solid, aqueous and non-	smog, fine dust, concrete, iron dust, ash,
volatile liquid aerosols up to 10 times the	cotton dust, fluoride, carbon fibres, gypsum,
respective limit values.	fibre glass, copper, nickel, soot, pollen,
	house dust, pet hair.

^{*}Please note that the above-mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

All respiratory protective devices fall into PPE category III (high risks).

Uvex accepts no liability for any possible harm or damage which may result from this information. This data sheet does not replace a detailed risk assessment nor seeking specialist advise.