

## Product data sheet for uvex rubiflex NB60S



Due to the cotton interlock supporting material, the uvex rubiflex S NB60S chemical protection glove is suitable for many applications where protection against chemicals as well as increased mechanical protection are required.

### Features

- Ergonomic fit
- Good grip
- Very good tactile feel

|                        |   |
|------------------------|---|
| <b>Material number</b> | 89647   |
| <b>Sizes</b>           | 8 - 11  |
| <b>Standard</b>        | EN 420:2003 + A1:2009, EN 388:2016, EN ISO 374-1:2016   |
| <b>Test chemicals</b>  | n-Heptane (J), Sodium hydroxide 40% (K), Ammonia water 25% (O), Hydrogen peroxide 30% (P), Formaldehyde 37% (T) |



**MADE IN GERMANY** 

### Manufacturer address

UVEX SAFETY Gloves GmbH & Co. KG  
 Elso-Klöver-Str. 6  
 D-21337 Lüneburg  
 uvex-safety.de

**Performance classes in accordance with EN 388** 2 1 2 1 X

**Performance classes in accordance with EN 407** X 1 X X X X

|                             |                      |
|-----------------------------|----------------------|
| <b>Outer material</b>       | Cotton interlock     |
| <b>Coating</b>              | Nitrile rubber (NBR) |
| <b>Coating surface area</b> | Fully coated         |
| <b>Coating thickness</b>    | 0.50 mm              |
| <b>Type</b>                 | With gauntlet        |
| <b>Colour</b>               | green                |
| <b>Glove length</b>         | 60 cm                |